ENVIROFALK

Envi GreenPURE
K 60-200

REVERSE OSMOSIS

ENVIROFALK

Envi GreenPURE

K 60-200

The compact Envi GreenPURE K reverse osmosis systems are efficient and space-saving, ideal for applications with special purity and space requirements. High-performance membranes efficiently remove impurities and ions, TOC and germs from softened water.

- **Simple integration and scalability:** The ready-to-connect systems for wall mounting save time when integrating into existing systems and are available in various output levels.
- **High-quality components:** Materials such as PP and stainless steel piping extend the service life for a long-term, safe supply of pure water.

Envi GreenPURE	K 60	K 120	K 200
Permeate output (l/h)	60	120	200
Desalination rate (%)	> 99	> 99	> 99
Efficiency/yield (%)	bis zu 80	bis zu 80	bis zu 80
Pre-filter	5" activated carbon filter	5" activated carbon filter	5" activated carbon filter
Dimensions (width x depth x height in mm)	500 x 400 x 850	500 x 400 x 850	500 x 400 x 850
Feed water quality	softened municipal water	softened municipal water	softened municipal water
Connection (feed water/permeate/concentrate)	DN 20/DN 15/DN 15	DN 20/DN 15/DN 15	DN 20/DN 15/DN 15
Feed water pressure (bar)	2,5 - 6	2,5 - 6	2,5 - 6
Maximum operating temperature (°C)	30	30	30
Ambient temperature (°C)	5 - 40	5 - 40	5 - 40
Electrical connection (V/Hz)	230/50	230/50	230/50
Power consumption (W)	0,55	0,55	0,55
Article no.	**320000**	**320001**	**320002**

Using water intelligently

EnviroFALK GmbH | Gutenbergstrasse 7 | 56457 Westerburg | +49 2663 9908 0 | info@envirofalk.com | **envirofalk.com**

ENVIROFALK

Options, spare parts and consumables

Spare parts and consumables	K 60	K 120	K 200
5“ Filter cartridge 5 µm with activated carbon	455099	455099	455099
Membrane element	410180	410177	729795

Using water intelligently
EnviroFALK GmbH | Gutenbergstrasse 7 | 56457 Westerburg | +49 2663 9908 0 | info@envirofalk.com | **envirofalk.com**